



TSPFS-1 **XX** - **S** - **02** - **X** - **LF**
(A) **(B)** **(C)** **(D)** **(E)**

- A. Pins Per Row
- 05,07,08,10,13,15
- B. Row Specification
- S = Single Row
- C. Pin Options
- 02
- D. Plating Options
- F = Gold Flash
- T = Tin
- FT = Gold Flash/Tin
- E. Lead Free

Specifications:
 Current Rating: 3.0 Ampere AC/DC
 Voltage Rating: 250V AC/DC
 Insulation Resistance: 1000M Ohms Min.
 Dielectric Withstanding: 600V AC
 Contact Resistance: 20M Ohms Max.
 Operation Temperature: -40°C to +105°C

Materials:
 Contact Material: Copper Alloy
 Insulator Material: Polyester UL 94V-0, PBT

Products are non-cancellable/ non-returnable.
 Parts are subject to change without notice.

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF Major League Electronics. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF Major League Electronics IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:		NAME	DATE	
DIMENSIONS ARE IN INCHES		DRAWN	GWE 12/14/22	
TOLERANCES:		CHECKED	NDC 12/14/22	
ONE DECIMALS ±.100		ENG APPR.		
TWO DECIMALS ±.010		MFG APPR.		TITLE: TSPFS-1 SINGLE ROW SIZE DWG. NO. C REV A
THREE DECIMALS ±.005		INTERPRET GEOMETRIC TOLERANCING PER: MATERIAL		
FOUR DECIMALS ±.002		FINISH		SCALE 6:1
NEXT ASSY	USED ON	DO NOT SCALE DRAWING		SHEET 1 OF 1
APPLICATION				